KENWOOD

NEXEDGE®

One Radio with Multi-Protocol Support

NX-3720HG/3820HG
NX-3920G/3921G

NXDN® DMR Gen2 Bluetooth® GPS FleetSync® DMR T3&S DMR Auto Slot Select

MULTI-PROTOCOL DIGITAL & ANALOG MOBILE RADIOS

This adaptable mobile radio supports both NXDN® and DMR digital protocols as well as mixed digital/FM analog operation, enabling it to serve with distinction in a wide range of enterprise and operation-critical applications. Designed with flexibility in mind, it's packed with convenient features like Bluetooth® for hands-free operation and built-in GPS. This model offers greater freedom of installation, the radio's front panel can be used as a remote control head (this requires an optional upgrade, to be available in the future). Additionally, for expansion capability a software license certification system facilitates extensive customization.

Features

Multi-protocol digital radio: Designed to operate under NXDN® or DMR digital, and FM analog protocols
NXDN Conventional and Type-C & Gen2 Trunking
DMR Tier 2 Conventional & Site Roaming
DMR Auto Slot Select
DMR Tier 3 Trunking
Mixed Digital & FM Analog Operation allows gradual migration at your own pace
4-Line Basic Frame (2-Line Main/Sub-LCD, icon & key guide) / 14 Characters
4-Line Text Message Frame (2 Lines of Text, icon & key guide)
7-color LED Bar Indicator
Remote Control Head (Option)
Optional DES and AES Encryption
External and Internal Speaker Switching
Built-in Bluetooth® for hands-free operation for IoT applications - Applicable Bluetooth profiles: HSP (Headset Profile) and SPP (Serial Port Profile)
Renowned KENWOOD Audio Quality achieved with Active Noise Reduction (ANR) that utilizes built-in DSP
Built-In GPS Receiver for effective fleet and incident management
IP54 and MIL-STD-810 C/D/E/F/G
4 Watts Audio Output Power
512 CH/128 Zones
1000 Channel option
Paging Call
Emergency Call
Status/Text Message
Remote Stun/Kill/Check

Digital – NXDN® Mode

NXDN Conventional
NXDN Type-C & Gen2 Trunking
6.25 & 12.5 kHz Channels
Advanced GPS
Remote Monitor
All Group Call
Over-the-Air Alias (OAA)
Over-the-Air Programming (OTAP)

Digital – DMR Mode

Two-slot TDMA in 12.5kHz channels
DMR Tier 2 Conventional / Site Roaming
DMR Auto Slot Select
S-Trunking (Ver. UP) DMR Tier 3 Trunking
Call Interruption
Dual-slot Direct Mode
Optional ARC4 Encryption

Analog – FM Mode

Conventional & LTR Trunking
FleetSync/II: PTT ID ANI / Caller ID Display, Selective Group Call, Emergency Status Text Messages
MDC-1200: PTT ID ANI / Caller ID Display, Emergency, Radio Check /Inhibit
QT / DQT, DTMF, 2-Tone
Built-in Voice Inversion Scrambler

Multi-Protocol

Unsurpassed interoperability for Enterprise radio users with the freedom to migrate at your own pace.

Gen2

Scalable server-based system architecture for management of NEXEDGE wide area digital communications systems.

Klarity

The ultimate level of sound clarity technology combining Optimization, advanced Sound Analysis and Active Noise Reduction.

Accessories

All accessories may not be available in all markets.
Contact an authorized Kenwood dealer for details and complete list of all accessories.

KMC-9C/59C
Desktop Microphone

KCT-23
DC Power Cable
M: 10ft (3m) / M3: 23ft (7m)

KLF-2
Line Filter

KMB-34
Mounting Case
for KPS-15

KMC-65M
Microphone

KCT-60
Connection Cable
(D-sub 15 to Molex
15 Pin Connector)

KMB-10
Key Lock Adapter

KPG-180AP
OTAP Manager

KMC-66M
Keypad Microphone

KCT-71
Remote Control Cablr
(M2: 17ft M3: 25ft M4: 1.6ft)

KRA-40G
GPS Active Antenna

KRK-18HM
Interface Kit for a
Control Head

KCT-18
Ignition Sense Cable
(Requires KCT-60)

KCT-72
External Accessory
Connection Cable
for KRK-18HM

KPS-15
DC Power Supply
(23A max)

KRK-19BM
Interface Kit for
an RF Deck

Specifications

General	NX-3720HG	NX-3820HG	NX-3920G	NX-3921G
Frequency Range	136-174 MHz	Type 1 450-520 MHz Type 2 400-470 MHz	TX/RX: 851-870 MHz TX:806-825 MHz	TX/RX: 935-941 MHz TX: 896-902 MHz
Max. Channels Per Radio	Up to 1000 CH with option			
Number of Channels	512			
Number of Zones	128			
Channel Spacing Analog Digital	 12.5/15/25*/30* kHz 6.25 kHz/12.5 kHz	 12.5/25* kHz 6.25 kHz/12.5 kHz	 12.5/25 kHz 6.25 kHz/12.5 kHz	 12.5 kHz 6.25 kHz/12.5 kHz
Power Supply	13.6 V DC ±15%			
Current Drain Standby RX TX	 0.45 A 2.3 A 12 A			
Operating Temperature	-22°F to +140°F (-30°C to +60°C)			
Frequency Stability	± 0.5 ppm			
Dimensions Radio with Control Head	(W x H x D) Projections Not Included 6.30 x 1.69 x 6.30 in (160 x 43 x 160 mm)			
Weight Radio Radio with Control Head	 2.65 lbs (1.2 kg)			
FCC ID Type 1 Type 2	 K44479200	 K44479300 K44479301	 K44502600	 K44502601
IC Certification Type 1 Type 2	 282F-479200	 282F-479301	 282F-502600	 282F-502601

*25/30 kHz in VHF/UHF Bands (except T-Band) are not included in the models sold in the USA or US territories.
** NX-3920G only
Analog measurements made per TIA603. Specifications are measured according to applicable standards.
Specifications shown are typical and subject to change without notice, due to advancements in technology.

Receiver	NX-3720HG	NX-3820HG	NX-3920G	NX-3921G
Sensitivity NXDN* 6.25 kHz Digital (3% BER) NXDN*12.5 kHz Digital (3% BER) DMR 12.5 KHz Digital (5% BER) DMR 12.5 KHz Digital (1% BER) Analog (12dB SINAD)	 0.20 µV 0.25 µV 0.30 µV 0.45 µV 0.25 µV			
Selectivity Analog @ 12.5kHz Analog @ 25kHz	 70 dB 80 dB			 60 dB 70 dB
Intermodulation	70 dB			
Spurious Rejection	80 dB			
Audio Distortion	2%			
Audio Output Power	4 W/4 Ω			

Transmitter	NX-3720HG	NX-3820HG	NX-3920G	NX-3921G
RF Power Output (High / Mid / Low)	50 W / 30 W / 5 W	45 W /30 W / 5 W		15 W / 5 W
Spurious Emission	73 dB	75 dB		-70 dB
FM Hum & Noise Analog @ 12.5kHz Analog @ 25kHz	 40 dB 45 dB			
Audio Distortion	2%			
Digital Protocol	ETSI TS 102 361-1, -2, -3, -4			
Emission Designator	16K0F3E*, 14K0F3E**, 11K0F3E, 8K30F1E, 8K30F1D, 8K30F7W, 7K60FXD, 7K60FXE, 4K00F1E, 4K00F1D, 4K00F7W, 4K00F2D			

The Bluetooth word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc.
NXDN* is a registered trademark of JVCKENWOOD Corporation and Icom Inc.
NEXEDGE* & FleetSync* are a registered trademarks of JVCKENWOOD Corporation.
All other trademarks are the property of their respective holders.

MIL-STD & IP

MIL Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures	MIL 810G Methods/Procedures
Low Pressure	500.1/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II	500.5/Procedure I, II
High Temperature	501.1/Procedure I, II	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II	501.5/Procedure I, II
Low Temperature	502.1/Procedure I	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II	502.5/Procedure I, II
Temperature Shock	503.1/Procedure I	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II	503.5/Procedure I
Solar Radiation	505.1/Procedure I	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I	505.5/Procedure I
Rain	506.1/Procedure I, II	506.2/Procedure I, II	506.3/Procedure I, II	506.4/Procedure I, III	506.5/Procedure I, III
Humidity	507.1/Procedure I, II	507.2/Procedure II, III	507.3/Procedure II, III	507.4	507.5/Procedure II
Salt Fog	509.1/Procedure I	509.2/Procedure I	509.3/Procedure I	509.4	509.5
Dust	510.1/Procedure I	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I, III	510.5/Procedure I
Vibration	514.2/Procedure VIII, X	514.3/Procedure I	514.4/Procedure I	514.5/Procedure I	514.6/Procedure I
Shock	516.2/Procedure I, II, V	516.3/Procedure I, IV, V	516.4/Procedure I, IV, V	516.5/Procedure I, IV, V	516.6/Procedure I, IV, V
International Protection Standard					
Dust & Water Protection*1	IP54, IP55*2				

*1 Applicable microphone must be connected to the radio, and all accessory connectors must be covered. *2 IP54: RF Deck; IP55: Remote Control Head.

JVCKENWOOD USA Corporation
Communications Sector Headquarters
1440 Corporate Drive | Irving, TX 75038

Order Administration/Distribution
P.O. BOX 22745, 2201 East Dominguez St., Long Beach, CA 90801-5745
www.kenwood.com/usa

JVCKENWOOD Canada Inc.
Canadian Headquarters and Distribution
6070 Kestrel Road, Mississauga, Ontario, Canada L5T 1S8
www.kenwood.com/ca

KENWOOD Communications
Global Website
comms.kenwood.com

JQA-1205 091
ISO9001 Registered
Communications Systems Business Unit
JVCKENWOOD Corporation

ADS#18119 Print in U.S.A.